

5STARS 1 CA/M



Part number	05086294
Lampholder:	G12
Light Source:	METAL HALIDE LAMPS
Wattage:	1x150 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 66
IK-J-xxIP:	IK08 7J xx5
Power factor:	COS ϕ \geq 0,9
Optic:	ASYMMETRIC MEDIUM CIRCLE REFLECTOR
Ta MIN luminaire:	-20°
Ta MAX luminaire:	30°




Description


Discharge lamp floodlight for indoor and outdoor lighting, comprising:

- Polyester powder coated die-cast aluminium housing
- Flat tempered glass diffuser
- Polished aluminium asymmetrical reflector
- Anti-ageing silicone gasket
- Fully integrated technopolymer trim hinged to the housing
- Waterproof cable gland M16x1.5 for cables \emptyset 5- \emptyset 10 mm
- Stainless steel external screws
- Powder coated steel bracket

PHOTOMETRIC DATA



TECHNICAL DRAWINGS




5STARS 1



14029094

Gliding support made of painted aluminium for the installation on 60 - 76 mm diam. posts . 1 luminaire 5STARS 1 / WIN+1.



14047194

Gliding support made of painted aluminium for the installation on 60- 76 mm diam. posts 2 opposed luminaires 5STARS 1 / WIN+1.