

## GUELL ZERO KIT S/M




<b>Part number</b>	06147585
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	15 W
<b>Finish:</b>	WH-RAL9010 / White RAL9010 / Glossy
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK06 1.2J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	SYMMETRIC MEDIUM REFLECTOR
<b>Lightsource lumen output:</b>	1888 lm
<b>Luminaire lumen output:</b>	1484 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	150000 h
<b>Ta MIN luminaire:</b>	-15°
<b>Ta MAX luminaire:</b>	35°



### Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
  - Flat tempered glass diffuser
  - Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
  - Very high performance symmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
  - Stainless steel external screws
  - Stainless steel locking springs for the glass
  - Powder coated steel bracket
  - Complete with 1 metre of cable H05RN-F 3G1 mm<sup>2</sup>
  - Versions of GUELL ZERO KIT are complete with 0.5 m arm with integrated connection box, suitable for through wiring

### PHOTOMETRIC DATA



### TECHNICAL DRAWINGS

