


5STARS 2 S/M




Part number	05069794
Lampholder:	E40
Wattage:	1x250 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 66
IK-J-xxIP:	IK08 5J xx5
Power factor:	COSφ ≥ 0,9
Optic:	SYMMETRIC MEDIUM REFLECTOR
Ta MIN luminaire:	-25°
Ta MAX luminaire:	35°




Description

- Discharge lamp floodlight for indoor and outdoor lighting, comprising:
- Polyester powder coated die-cast aluminium housing
 - Flat tempered glass diffuser
 - Polished aluminium symmetrical reflector
 - Gaskets made of silicone foam directly applied on glass without joints
 - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket
 - Shaped steel gear tray also designed as heat sink
 - Graduated goniometer for aiming purposes

PHOTOMETRIC DATA



TECHNICAL DRAWINGS



5STARS 2




14026520
5STARS 2 frosted glass, optional replacement for standard clear glass.



14012320
External anti-glare louvre painted aluminium grey.



14012420
External cowl painted aluminium grey.



14012520
Steel galvanised wire guard (18 Joule).



14044620
5STARS 2 strengthening bracket. Designed for single point fixing M12-M14 screw in centre of the bracket.



14012620
Single 5STARS 2 pole top fitting and outreach arm for Ø60-76mm poles.



14012720
Twin 5STARS 2 pole top fitting and outreach arm for Ø60-76mm poles.



14011594
1000mm extension arm in heavy gauge steel painted aluminium grey.