



MINIPERFETTO FOR BROADWAY 3000K

Design: Studio Tecnico Ivela



Product code	Colour
--------------	--------

749-261-16	Black
------------	-------

General Specifications

Product type	: Spotlights
Mounting type	: Lighting systems
Description	: Spotlight for Broadway lighting system, equipped with a high efficiency COB LED. It features an adjustable arm with triple junction, for cardan movements on all axes, in addition to the 350° orientation of the head. Both professional optics to get different beam angles, and optical devices for a better visual comfort are available as accessories.

Notes	: Max. 5 fittings on each 1300 mm Broadway profile. Max. 10 fittings on each 2300 mm Broadway profile.
-------	--

Indoor/outdoor lights	: Indoor
Applications	: Museums, Retail, Shopping centres, Showrooms

Lighting specifications

Lamp description	: LED 2400lm 18W 3000K
Nominal lumens on thermal regime	: 2400
Lamp wattage (W)	: 18
Color temperature (K)	: 3000

Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Reflector	: Mirror-metallized thermoplastic material
Thermal Dissipation	: Passive

Electrical Specifications

Glow wire (°C)	: 850
Driver	: Included
Driver mounting	: Integrated
Voltage (V)	: 220/240
Frequency (Hz)	: 50/60




Weight and Dimensions

Shape	: Cylindrical
Width (mm)	: 52
Height (mm)	: 162
Weight (Kg)	: 0.9

Optical Specifications

Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 30°
Horizontal orientation	: 350°
Note	: Honeycomb code 28-4022-30 to be used only together with screen code 28-3905-47. 24°, 45° (mirror metallized) optics are available on demand.

Unified Glare Rating (U.G.R.)	: <19
-------------------------------	-------



Accessories




28-3905-47
Closing
screen in
thermoplastic

28-3901-51
Professional
optic device
24°

28-3903-51
Professional
optic device
45°

28-3979-100
Satined gold
snoot

28-4022-30
Honeycomb

Lamps	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color rendering (CRI)
	LED	COB LED	18	2400	85

Pictures and Applications

