

## Ceiling Lights | 220-240 V | 1xE27 15185













l data		

Technical data	
Туре	Surface
Installation position	Wall lights - Ceiling
Installation environment	Outdoor
Lamp cap	1 x E27 Max 46W
Frequency	50-60 Hz
Optics	General Lighting
Light emission direction	downward
Safety class	2
IP	IP65
ĪK .	IK10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	4.050 Kg



Finishing diffe	user	
Material	PE	
Colour	neutral	



## Ceiling Lights | 220-240 V | 1xE27 15185

Double emission ceiling lights for outdoor application. Compatibility: LED lamp, compact fluo 30 W, halogen 46 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of  $4.050~\rm{kg}$ .

The device features protection class II and can be wall lights or ceilingmounted.

Illuminotechnical Features		
Light Output Ratio (LOR)	77 %	
Luminous flux (source)	700 lm	
Luminaire luminous flux	1480 lm	
Consumption	30 W	
Luminaire efficacy	63 lm/W	
Colour rendering index	100 Ra	

OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	180°

