
Pendant Luminaires | 220-240 V | 1xE27 15180



Technical data		
Туре	Surface	
Installation position	Ceiling	
Installation environment	Outdoor	
Lamp cap	1 x E27 Max 30W	
Frequency	50-60 Hz	
Optics	General Lighting	
Light emission direction	downward	
Safety class	2	
IP	IP65	
Glow wire test	650°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Fire Rated (BS 476 PT21 compliant)	No	
Induction	No	
Emergency mode	No	
Motion sensor	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Double emission	
Net weight	1.410 Kg	

Finishing casing				
Material	PE			
Colour	white			
Finishing diffu	iser			
	DE.			
Material	PE			

× • • • • • • •

Oh!_P65

Pendant Luminaires | 220-240 V | 1xE27 15180

Double emission pendant luminaires for outdoor application. Compatibility: LED lamp, halogen 30 W, compact fluo 14 W; lamp cap 1xE27.

The device body is made of pe and features a white finish; the diffuser is made of pe; the mounting frame is made of iron, processed by means of coating. The ingress protection degree is IP65; the total weight is of 1.410 kg.

The device features protection class II and can be ceiling-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	77 %
Luminous flux (source)	405 lm
Luminaire luminous flux	623 lm
Consumption	14 W
Luminaire efficacy	57 lm/W
Colour rendering index	100 Ra
OPTICAL	
Light distribution simmetry	Symmetrical

Light distribution simmetry	Symmetrical
C0/C180 optics	180°

