

## GUELL 2.5 A50/W




<b>Part number</b>	306205
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	118 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK07 3J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	Asymmetric Wide Reflector
<b>Lightsource lumen output:</b>	18127 lm
<b>Luminaire lumen output:</b>	13862 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	130000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	35°




### Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
  - Flat tempered glass diffuser
  - Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
  - Asymmetrical optic
  - Anti-ageing silicone gasket
  - Cable gland M20x1.5 for cables  $\varnothing$  10-  $\varnothing$  14 mm
  - Dimmable DALI
  - The versions with A50/W optics comprise LED modules and reflectors specifically studied for settings that require highly asymmetrical light distribution.
  - Stainless steel external screws
  - Fully integrated stainless steel aluminium spring clips
  - Powder coated steel bracket


### PHOTOMETRIC DATA




### TECHNICAL DRAWINGS



## GUELL 2.5



310963  
Cover GUELL 2.5



310965  
Protective grid GUELL 2.5



310982  
Wall mount support 1000 mm



310967  
Double pole top support GUELL 2.5



310966  
Single pole top support GUELL 2.5