

GUELL 2.5 C/I




| | |
|----------------------------------|----------------------------------|
| Part number | 306210 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 238 W |
| Finish: | GR-94 / Metallic grey / Textured |
| Insulation class: | I |
| Degree of protection: | IP 66 |
| IK-J-xxIP: | IK07 3J xx5 |
| CRI: | 80 |
| Kelvin: | 4000 |
| Power factor: | COS ϕ \geq 0,9 |
| Optic: | INTENSIVE CIRCLE REFLECTOR |
| Lightsource lumen output: | 33426 lm |
| Luminaire lumen output: | 27961 lm |
| L: | L70 |
| B: | B10 |
| Lifetime: | 130000 h |
| Ta MIN luminaire: | -20° |
| Ta MAX luminaire: | 30° |




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat tempered glass diffuser
 - Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Intensive circular optic
 - Anti-ageing silicone gasket
 - Cable gland M20x1.5 for cables \varnothing 10- \varnothing 14 mm
 - Analogue dimmable HF ballast, 1-10 V
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket


PHOTOMETRIC DATA




TECHNICAL DRAWINGS



GUELL 2.5



310963
Cover GUELL 2.5



310965
Protective grid GUELL 2.5



310982
Wall mount support 1000 mm



310967
Double pole top support GUELL 2.5



310966
Single pole top support GUELL 2.5