

## GUELL 2.5 S/W




<b>Part number</b>	306199
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	166 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 66
<b>IK-J-xxIP:</b>	IK07 3J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	SYMMETRIC WIDE REFLECTOR
<b>Lightsource lumen output:</b>	22284 lm
<b>Luminaire lumen output:</b>	20195 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	130000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	40°




### Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
  - Flat tempered glass diffuser
  - Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
  - Symmetrical lens
  - Anti-ageing silicone gasket
  - Cable gland M20x1.5 for cables  $\varnothing$  10-  $\varnothing$  14 mm
  - Analogue dimmable HF ballast, 1-10 V
  - Stainless steel external screws
  - Fully integrated stainless steel aluminium spring clips
  - Powder coated steel bracket


### PHOTOMETRIC DATA



### TECHNICAL DRAWINGS




## GUELL 2.5 S/W (166 W - 238 W)




310961  
Louvre GUELL 2.5 Symmetrical

## GUELL 2.5 A/W - S/W (166 W - 238 W)




310964  
GUELL 2.5 frosted glass

## GUELL 2.5



310963  
Cover GUELL 2.5



310965  
Protective grid GUELL 2.5



310982  
Wall mount support 1000 mm



310967  
Double pole top support GUELL 2.5



310966  
Single pole top support GUELL 2.5