

GUELL 3 S/W




| | |
|----------------------------------|----------------------------------|
| Part number | 06172894 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 238 W |
| Finish: | GR-94 / Metallic grey / Textured |
| Insulation class: | I |
| Degree of protection: | IP 66 |
| IK-J-xxIP: | IK07 3J xx5 |
| CRI: | 80 |
| Kelvin: | 4000 |
| Power factor: | COSφ ≥ 0,9 |
| Optic: | SYMMETRIC WIDE REFLECTOR |
| Lightsource lumen output: | 33234 lm |
| Luminaire lumen output: | 26947 lm |
| L: | L70 |
| B: | B10 |
| Lifetime: | 130000 h |
| Ta MIN luminaire: | -30° |
| Ta MAX luminaire: | 40° |




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat extra clear tempered glass diffuser
 - Very high performance symmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Anti-ageing silicone gasket
 - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket
 - Dimmable ballast on request
 - 3000 K and 5000 K available upon request

PHOTOMETRIC DATA



TECHNICAL DRAWINGS




GUELL 3 A/W - S/W



14452994
Frosted glass GUELL 3 (not suitable for 158 W).

GUELL 3 S/W




14454220
Louvre GUELL 3 Symmetrical (not suitable for 158 W).

GUELL 3




14452894
Cover



14452702
Protective grid




14453994
Wall mount support 1000 mm



14453794
Single pole top support GUELL 3 for poles \varnothing 60-76 mm/ \varnothing 2.36"-2.99".



14453894
Double pole top support GUELL 3 for poles \varnothing 60-76 mm/ \varnothing 2.36"-2.99"



14461104
GUELL 3 strengthening bracket. Suitable for one floodlight single point fixing M10 screw in centre of the bracket.