
Wall Lights | 220-240 V | topLED 19 W 700 mA | CRI 90 7609





Technical data	
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	upward
Power	19 W
Luminous flux (source)	2204 lm
Frequency	50 - 60 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
AC / DC	AC
Safety class	1
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	Yes
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Material	Aluminium	
Colour	black RAL 9005	
Processing	Coating	

rinishing unuser		
Material	PC	
Processing	Sandblasting	

linealight.com

28.02.2018

Tablet_W1

Wall Lights | 220-240 V | topLED 19 W 700 mA | CRI 90 7609


Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 48 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2204 lm, with a 116.0 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a black ral 9005 finish, processed by means of coating; the diffuser is made of PC with a sandblasting treatment. The ingress protection degree is IP40; the total weight is of 1,048 kg. The power supply driver is included in the delivery.

The total absorbed power is 19 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features		
Light Output Ratio (LOR)	53 %	
Luminous flux (source)	2204 lm	
Luminaire luminous flux	1169 lm	
Consumption	15 W	
Luminaire efficacy	77 lm/W	
Colour temperature	3000 K	
Standard Deviation of Colour Matching	3 Step MacAdam	
Colour rendering index	90 Ra	
Life / Failure ratio	L80C0B20	
UGR		
	S=0.25H	
Reflection factor	70/50/20	
UGR transversal	< 25	
UGR axial	< 25	
OPTICAL		
Light distribution simmetry	Symmetrical	
Ottica C0/C180	98°	



	\land			
0.5	1.17 1.15	E(0°) E(C90) E(C0)	49.4° 49.0°	1829 264 272
1.0	2.33 2.30	E(0°) E(C90) E(C0)	49.4° 49.0°	457 66 68
1.5	3.50 3.45	E(0°) E(C90) E(C0)	49.4° 49.0°	203 29 30
2.0	4.67 4.60	E(0°) E(C90) E(C0)	49.4° 49.0°	114 17 17
2.5	5.83 5.75	E(0°) E(C90) E(C0)	49.4° 49.0°	73 11 11
3.0	7.00 6.90	E(0°) E(C90) E(C0)	49.4° 49.0°	51
Distance [m]	Cone diameter [m]		Illumina	nce [lx

C0/C180 (Half-peak divergence: 98.0°)
C90/C270 (Half-peak divergence: 98.8°)

Tablet_W1 | Wall Lights | Accessories 7609

Code

KIT0042

Finish

Black



Bracket L=239mm, H=5mm, D=50mm. Material:Aluminium, colour:black RAL 9005, processing:Coating.