


Oxygen_W1



Wall Lights | 220-240 V | topLED 17 W 500 mA | DALI | CRI 90
8187



Technical data	
Designer	Pio e Tito Toso
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	17 W
Luminous flux (source)	2021 lm
Frequency	60 - 50 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Dimmable article	DALI
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	PU
Colour	Yellow/white

Finishing diffuser	
Material	PMMA
Colour	transparent
Processing	Laser engravings



Wall Lights | 220-240 V | topLED 17 W 500 mA | DALI | CRI 90
8187

Double emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 35 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2021 lm, with a 118.9 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of pu and features a yellow/white finish; the diffuser is made of pmma with a laser engravings treatment. The ingress protection degree is IP40; The power supply driver is included in the delivery.


The total absorbed power is 17 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	39 %
Luminous flux (source)	2021 lm
Luminaire luminous flux	789 lm
Consumption	17 W
Luminaire efficacy	46 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20



Oxygen_W1 | Wall Lights | Accessories
8187



Dimmer
Bluetooth, 220-240V

Code
KIT0079