




Wall Lights | topLED 19 W 220-240 V AC | CRI 90  
7753



Technical data	
Designer	Pio e Tito Toso
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	19 W
Luminous flux (source)	1530 lm
Tensione	220-240V
Frequency	50-60 Hz
CCT / Tonalità	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Aluminium
Colour	black RAL 9005
Processing	Coating

Finishing diffuser	
Material	PC
Colour	transparent



Wall Lights | topLED 19 W 220-240 V AC | CRI 90  
7753

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 40 topLED LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1530 lm, with a 80.5 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a black ral 9005 finish, processed by means of coating; the diffuser is made of PC. The ingress protection degree is IP40;



The total absorbed power is 19 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	82 %
Luminous flux (source)	1530 lm
Luminaire luminous flux	1258 lm
Consumption	19 W
Luminaire efficacy	66 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20 80H


UGR	
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	> 28
UGR axial	> 28

OPTICAL	
Light distribution simmetry	Symmetrical 2
Ottica C0/C180	106°
Ottica C90/C270	110°





Quad\_W | Wall Lights | Accessories  
7753



Dimmer  
PUSH DIM, 220-240V

**Code**  
KIT0026