

Product code	Colour
--------------	--------

252-210-21	Mat white
------------	-----------

### General Specifications

Product type	: Downlights
Mounting type	: Ceiling - recessed
Description	: Ceiling downlight for accent lighting, designed for the last generation of LEDs. It is characterized by an extremely shallow recessed depth. Protection rating IP 43. The 500mA 20W constant current LED driver must be ordered separately. Max. 8 fittings can be connected.

Indoor/outdoor lights	: Indoor
Applications	: Corridors, Passage areas, Residential, Showrooms

### Lighting specifications

Average lamp life (h)	: 50.000
Lamp description	: LED 200lm 2W 3000K
Nominal lumens on thermal regime	: 200
Lamp wattage (W)	: 2
Color temperature (K)	: 3000

### Physical Specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted
Thermal Dissipation	: Passive

### Electrical Specifications

Glow wire (°C)	: 850
Driver	: Separate item
Driver mounting	: Remote


### Weight and Dimensions

Shape	: Round
External diameter (mm)	: 41
False ceiling thickness (mm)	: 1-30 mm
Height (mm)	: 45
Cutout shape	: Round
Cutout Diameter (mm)	: 36
Recessed depth (mm)	: 45


### Optical Specifications

Aiming	: Fixed
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 14°

## Drivers



81-04019  
Driver 500mA  
constant  
current

Lamps	Lamp categories	Lamp type	Lamp wattage (W)	Nominal lumens on thermal regime (lm)
	LED	LED	2	200

## Pictures and Applications

