

DULUX S 7 W/865 G23

OSRAM DULUX S | Short CFLni, with 2-pin base for CCG operation



Areas of application

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

Product benefits

- Extremely economical
- Good quality of light
- Extremely low profile
- Long service life
- Improved maintenance

Product features

- Average life: 10,000 h
- Color rendering index R_a for lamps with white light: 80...89
- Also available in red, green and blue
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base



Product datasheet

Technical data

Photometrical data


Color rendering index Ra	80...89
--------------------------	---------

Lifespan


Nominal lamp life time	10000 h
------------------------	---------

Equipment / Accessories


- Suitable for operation on conventional control gear



Circuit diagram



Circuit diagram



Circuit diagram

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321580672	DULUX S 7 W/865 G23	Shipping carton box 10 Pieces Folding carton box	190 mm x 53 mm x 152 mm	1.53 dm ³	413.00 g
4008321582805	DULUX S 7 W/865 G23	Shipping carton box 50 Pieces Folding carton box	240 mm x 190 mm x 153 mm	6.98 dm ³	1987.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.