## Ambra Cristallo\_P

## Pendant Luminaires | 220-240 V | 1xR7s **4506**



max 90		
	37	61

♥ أ 🖓 🖓

Technical data			
Installation position	Ceiling		
Installation environment	Indoor		
Power	1 x 160 W		
Lamp cap	1 x R7s		
Frequency	50-60 Hz		
Optic	Diffused		
Light emission direction	downward		
Safety class	1		
IP	IP20		
Glow wire test	850°		
Direct mounting on normally flammable surfaces	Yes		
CE	Yes		
ETL	No		
Induzione	No		
Emergency mode	No		
Directional	No		
Tilting	No		
Walk-over	No		
Drive-over	No		
Cable included	No		
Resin potting	No		

Finishing casin	g
Material	Iron
Colour	nickel
Processing	Electroplating
Finishing diffus	er
Material	Glass - Glass
Colour	white - white
Processing	Sandblasting - Sandblasting
Finishing moun	ting frame
Material	Iron
Colour	nickel
Processing	Electroplating

## Ambra Cristallo\_P

Pendant Luminaires | 220-240 V | 1xR7s 4506

Single emission pendant luminaires for indoor application. Halogen lamp included 160W, lamp cap 1xR7s.

The device body is made of iron and features a nickel finish, processed by means of electroplating; the diffuser is made of glass with a sandblasting treatment; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a nickel finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 7.130 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features				
Luminous flux (source)	3100 lm			
Colour temperature	2950 K			
Colour rendering index	100 Ra			