
Pendant Luminaires | 220-240 V | 2xE27 4432





Technical data	
Installation position	Ceiling
Installation environment	Indoor
Lamp cap	2 x E27 Max 57W
Frequency	50-60 Hz
Optic	Diff. + Diff. + Diff.
Light emission direction	downward
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casin	g	
Material	Iron	
Colour	nickel	
Processing	Electroplating	
Finishing diffus	er	
Material	Glass	
Colour	white	
Processing	Sandblasting	
Finishing moun	ting frame	
Material	Iron	
Colour	nickel	
Processing	Electroplating	

Pendant Luminaires | 220-240 V | 2xE27 4432

Single emission pendant luminaires for indoor application. Compatibility: LED lamp, compact fluo 20 W, halogen 57 W; lamp cap 2xE27.

The device body is made of iron and features a nickel finish, processed by means of electroplating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a nickel finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 3.860 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features		
Luminous flux (source)	4430 lm	
Colour temperature	2500 K	
Colour rendering index	100 Ra	