## Ceiling Lights | 220-240 V | 2xE27 7656



| Technical data                                 |                  |
|--|------------------|
| <br>Туре                                       | Surface          |
| Installation position                          | Ceiling          |
| Installation environment                       | Indoor           |
| Lamp cap                                       | 2 x E27 Max 46W  |
| Frequency                                      | 50-60 Hz         |
| Optics   | General Lighting |
| Light emission direction                       | downward         |
| Safety class                                   | 1                |
| IP   | IP40             |
| Glow wire test                                 | 850°             |
| Direct mounting on normally flammable surfaces | Yes              |
| CE   | Yes              |
| ETL  | No               |
| Fire Rated (BS 476 PT21 compliant)             | No               |
| Induction                                      | No               |
| Motion sensor                                  | No               |
| Directional                                    | No               |
| Tilting  | No               |
| Walk-over                                      | No               |
| Drive-over                                     | No               |
| Cable included                                 | No               |
| Resin potting                                  | No               |
| Net weight                                     | 3.950 Kg         |

223 Ø 499

| Finishing casing |                         |  |
|------------------|-------------------------|--|
| Material         | Iron                    |  |
| Colour           | embossed white RAL 9003 |  |
| Processing       | Coating                 |  |
|                  |                         |  |
| Finishing diffus | er                      |  |
| Material         | PE                      |  |
| Colour           | neutral                 |  |

Double emission ceiling lights for indoor application. Compatibility: LED lamp, halogen 46 W, compact fluo 20 W; lamp cap 2xE27.

The device body is made of iron and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pe. The ingress protection degree is IP40; the total weight is of 3.950 kg.

The device features protection class I and can be ceiling-mounted.

| 71 %    |
|---------|
| 1400 lm |
| 1001 lm |
| 92 W    |
| 15 lm/W |
| 2500 K  |
| 100 Ra  |
|         |

