




Wall Lights | 220-240 V | topLED 30 W | CRI 90  
90324



Technical data	
Type	Surface
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	30 W
Source lumens	3306 lm
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
AC / DC	AC
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission



Wall Lights | 220-240 V | topLED 30 W | CRI 90  
**90324**

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 72 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3306 lm, with a 110.2 lm/W nominal luminous efficacy.

The mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40;

The total absorbed power is 30 W.

The device features protection class I and can be wall lights or ceiling-mounted.

#### **Illuminotechnical Features**

Source lumens	3306 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra

#### **LED Life / Failure Ratio**

L80 B20 C0 80000h