





Wall Lights | 220-240 V | topLED 21 W 500 mA | CRI 90
8459



| Technical data | |
|--|------------------|
| Type | Surface |
| Installation position | Wall lights |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward |
| Power | 21 W |
| Source lumens | 1976 lm |
| Frequency | 60 - 50 Hz |
| CCT / Tone | 3000 K |
| Colour rendering index | 90 Ra |
| Safety class | 1 |
| IP | IP40 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Driver included | Driver |
| Dimmable article | Phase cut |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Single emission |
| Net weight | 1.340 Kg |

| Finishing diffuser | |
|--------------------|--------------|
| Material | PC |
| Processing | Sandblasting |



Wall Lights | 220-240 V | topLED 21 W 500 mA | CRI 90
8459

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 24 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1976 lm, with a 94.1 lm/W nominal luminous efficacy.

The diffuser is made of PC with a sandblasting treatment; the mounting frame is made of aluminium, with a gold finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 1.340 kg.

The total absorbed power is 21 W.

The device features protection class I and can be wall lights-mounted.

| Illuminotechnical Features | |
|---------------------------------------|----------------|
| Light Output Ratio (LOR) | 60 % |
| Source lumens | 1976 lm |
| Delivered lumens | 1188 lm |
| Consumption | 21 W |
| Luminaire efficacy | 56 lm/W |
| Colour temperature | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 90 Ra |
| LED Life / Failure Ratio | |
| L80 B20 C0 80000h | |