




Wall Lights | 220-240 V | topLED 21 W 500 mA | CRI 90
8458



Technical data	
Type	Surface
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	21 W
Source lumens	1976 lm
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Dimmable article	Phase cut
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	1.340 Kg

Finishing diffuser	
Material	PC
Processing	Sandblasting



Wall Lights | 220-240 V | topLED 21 W 500 mA | CRI 90
8458

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 24 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1976 lm, with a 94.1 lm/W nominal luminous efficacy.

The diffuser is made of PC with a sandblasting treatment; the mounting frame is made of aluminium, with a brown finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 1.340 kg.

The total absorbed power is 21 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	60 %
Source lumens	1976 lm
Delivered lumens	1188 lm
Consumption	21 W
Luminaire efficacy	56 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
LED Life / Failure Ratio	
L80 B20 C0 80000h	