




Ceiling Lights | 220-240 V | topLED 22 W 500 mA
CRI 80
8334



| Technical data | |
|--|-----------------------|
| Type | Surface |
| Installation position | Wall lights - Ceiling |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward |
| Power | 22 W |
| Source lumens | 2450 lm |
| Frequency | 60 - 50 Hz |
| CCT / Tone | 3000 K |
| Colour rendering index | 80 Ra |
| AC / DC | AC |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Driver included | Driver |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Single emission |
| Net weight | 1.8 Kg |
| Electrostatic discharge protection | No |
| Surge protection | No |

| Finishing casing | |
|------------------|-------------------------|
| Material | Aluminium |
| Colour | embossed white RAL 9003 |
| Processing | Coating |

| Finishing diffuser | |
|--------------------|---------|
| Material | PC |
| Colour | opaline |

Ceiling Lights | 220-240 V | topLED 22 W 500 mA | CRI 80
8334

Single emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 2450 lm, with a 111.4 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of PC. The ingress protection degree is IP20; the total weight is of 1.8 kg.

The total absorbed power is 22 W.

The device features protection class I and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features

| | |
|---------------------------------------|----------------|
| Light Output Ratio (LOR) | 72 % |
| Source lumens | 2450 lm |
| Delivered lumens | 1764 lm |
| Consumption | 25 W |
| Luminaire efficacy | 70 lm/W |
| Colour temperature | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 80 Ra |

LED Life / Failure Ratio


| |
|------------------|
| L70 B20 C0 72.5h |
|------------------|

UGR

| | |
|-------------------|----------|
| X=4H Y=8H | S=0.25H |
| Reflection factor | 70/50/20 |
| UGR transversal | < 22 |
| UGR axial | < 22 |

OPTICAL

| | |
|-----------------------------|-------------|
| Light distribution simmetry | Symmetrical |
| C0/C180 optics | 112° |



| Distance [m] | Cone diameter [m] | illuminance [lx] |
|--------------|-------------------|---------------------------------------|
| 0.5 | 1.49 1.54 | E(0°) 2483 E(C90) 216 E(C0) 201 |
| 1.0 | 2.98 3.08 | E(0°) 621 E(C90) 54 E(C0) 50 |
| 1.5 | 4.46 4.62 | E(0°) 276 E(C90) 24 E(C0) 22 |
| 2.0 | 5.95 6.16 | E(0°) 155 E(C90) 13 E(C0) 13 |
| 2.5 | 7.44 7.70 | E(0°) 99 E(C90) 9 E(C0) 8 |
| 3.0 | 8.93 9.24 | E(0°) 69 E(C90) 6 E(C0) 6 |

— C0/C180 (Half-peak divergence: 114.0°)
— C90/C270 (Half-peak divergence: 112.2°)