

Wall Lights | 220-240 V | 1x2G11 6724











| | 80 |
|-----|-------|
| 449 | 1 |

| Technical data | |
|--|---------------------|
| Installation position | Wall lights |
| Installation environment | Indoor |
| Power | 1 x 36 W |
| Lamp cap | 1 x 2G11 |
| Frequency | 60 - 50 Hz |
| Optics | General Lighting |
| Light emission direction | downward and upward |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Driver included | Yes |
| Induzione | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Net weight | 1.665 Kg |

| Finishing casing | I | |
|--------------------------|----------------|--|
| Material | Iron | |
| Colour | chrome | |
| Processing | Electroplating | |
| | | |
| Finishing diffus | er | |
| Material | Glass | |
| Colour | white | |
| Processing | Sandblasting | |
| | | |
| Finishing mounting frame | | |
| Material | Iron | |
| Colour | white | |
| Processing | Coating | |



Wall Lights | 220-240 V | 1x2G11 **6724**

Double emission wall lights for indoor application. Fluorescent lamp included 36W, lamp cap 1x2G11.

The device body is made of iron and features a chrome finish, processed by means of electroplating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.665 kg. The power supply driver is included in the delivery.

The device features protection class I and can be wall lights-mounted.

| Illuminotechnical Features | |
|----------------------------|---------|
| Light Output Ratio (LOR) | 33 % |
| Luminous flux (source) | 2900 lm |
| Luminaire luminous flux | 973 lm |
| Consumption | 35 W |
| Luminaire efficacy | 82 lm/W |
| Colour temperature | 3000 K |
| Colour rendering index | 80 Ra |

