

## Wall Lights | 220-240 V | 1x2G11 6726











	80
449	69

Technical data	
Installation position	Wall lights
Installation environment	Indoor
Power	1 x 36 W
Lamp cap	1 x 2G11
Frequency	60 - 50 Hz
Optics	General Lighting
Light emission direction	downward and upward
Safety class	1
IP .	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	1.665 Kg

Finishing casing		
Material	Iron	
Colour	grey RAL 9006	
Processing	Coating	
Finishing diffus	er	
Material	Glass	
Colour	white	
Processing	Sandblasting	
Finishing moun	ing frame	
Material	Iron	
Colour	white	
Processing	Coating	



## Wall Lights | 220-240 V | 1x2G11 **6726**

Double emission wall lights for indoor application. Fluorescent lamp included 36W, lamp cap 1x2G11.

The device body is made of iron and features a grey ral 9006 finish, processed by means of coating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.665 kg. The power supply driver is included in the delivery.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	33 %
Luminous flux (source)	2900 lm
Luminaire luminous flux	973 lm
Consumption	35 W
Luminaire efficacy	82 lm/W
Colour temperature	3000 K
Colour rendering index	80 Ra

