Wall Lights | 220-240 V | 1x2G11 6727







| inishing casin | • |
|------------------|--------------|
| Material | Iron |
| Processing | Coating |
| | |
| Finishing diffus | ser |
| Material | Glass |
| Colour | white |
| Processing | Sandblasting |
| | |
| Finishing mour | ting frame |
| Material | Iron |
| Colour | white |
| Processing | Coating |

| Technical data | | |
|--|---------------------|--|
| Installation position | Wall lights | |
| Installation environment | Indoor | |
| Power | 1 x 36 W | |
| Lamp cap | 1 x 2G11 | |
| Frequency | 60 - 50 Hz | |
| Optics | General Lighting | |
| Light emission direction | downward and upward | |
| Safety class | 1 | |
| IP | IP20 | |
| Glow wire test | 850° | |
| Direct mounting on normally flammable surfaces | Yes | |
| CE | Yes | |
| ETL | No | |
| Driver included | Yes | |
| Induzione | No | |
| Emergency mode | No | |
| Directional | No | |
| Tilting | No | |
| Walk-over | No | |
| Drive-over | No | |
| Cable included | No | |
| Resin potting | No | |
| Net weight | 1.665 Kg | |
| | | |

Double emission wall lights for indoor application. Fluorescent lamp included 36W, lamp cap 1x2G11.

The device body is made of iron, processed by means of coating; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.665 kg. The power supply driver is included in the delivery.

The device features protection class I and can be wall lights-mounted.

| 33 % |
|---------|
| 2900 lm |
| 973 lm |
| 35 W |
| 82 lm/W |
| 3000 K |
| 80 Ra |
| |

