
Pendant Luminaires | 220-240 V | 1xE27 1018



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Lamp cap	1 x E27 Max 77W
Frequency	50-60 Hz
Optic	Diff. + Diff. + Diff.
Light emission direction	downward and
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No



Material Iron Colour nickel Processing Electroplating Finishing diffuser	Finishing casin	3
Processing Electroplating Finishing diffuser Glass Colour white	Material	Iron
Finishing diffuser Material Glass Colour white	Colour	nickel
Material Glass Colour white	Processing	Electroplating
Material Glass Colour white		
Colour white	Finishing diffus	er
	Material	Glass
Processing Silk-screening	Colour	white
	Processing	Silk-screening
	Finishing moun	ting frame

Finishing mounting frame	
Material	Iron
Colour	nickel
Processing	Electroplating

Double emission pendant luminaires for indoor application. Compatibility: LED lamp, compact fluo 20 W, halogen 77 W; lamp cap 1xE27.

The device body is made of iron and features a nickel finish, processed by means of electroplating; the diffuser is made of glass with a silkscreening treatment; the mounting frame is made of iron, with a nickel finish, processed by means of electroplating. The ingress protection degree is IP20; the total weight is of 3.415 kg.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features		
Luminous flux (source)	2620 lm	
Colour temperature	2800 K	
Colour rendering index	100 Ra	