
Wall Lights | 220-240 V | 1xR7s 1024

• . . . •



Technical data	
Installation position	Wall lights
Installation environment	Indoor
Power	1 x 120 W
Lamp cap	1 x R7s
Frequency	50-60 Hz
Optics	General Lighting
Light emission direction	frontal
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	1.642 Kg

Finishing seein	-
Finishing casin	g
Material	Wood - Iron
Colour	cherry wood - nickel
Processing	Electroplating
Finishing diffus	ar.
Fillishing ullus	
Material	Glass - Glass
Colour	white - white
Processing	Sandblasting - Sandblasting
Finishing moun	ting frame
	•
Material	Iron
Colour	white
Processing	Coating

1024

Double emission wall lights for indoor application. Halogen lamp included 120W, lamp cap 1xR7s.

The device body is made of iron and features a nickel finish, processed by means of electroplating The device body is made of wood and features a cherry wood finish; the diffuser is made of glass with a sandblasting treatment; the diffuser is made of glass with a sandblasting treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.642 kg.

The device features protection class I and can be wall lights-mounted.

ight Output Ratio (LOR)	67 %
uminous flux (source)	2250 lm
uminaire luminous flux	1521 lm
Consumption	120 W
uminaire efficacy	18 lm/W
olour temperature	2900 K
Colour rendering index	100 Ra

Light distribution simmetry

Ottica C90/C270

114°

Asymmetrical

