


Box_W1



100-265 V | topLED 6 W 250 mA | CRI 80
8770



| Technical data | |
|--|------------------|
| Installation position | Wall lights |
| Installation environment | Indoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | upward |
| Power | 6 W |
| Luminous flux (source) | 561 lm |
| Frequency | 60 - 50 Hz |
| CCT / Tonaltà | 3000 K |
| Colour rendering index | 80 Ra |
| Safety class | 1 |
| IP | IP40 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | No |
| CE | No |
| ETL | No |
| Driver included | Yes |
| Induzione | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Net weight | 0.55 Kg |

| Finishing diffuser | |
|--------------------|---------|
| Material | PMMA |
| Colour | opaline |

| Finishing mounting frame | |
|--------------------------|-------------------------|
| Material | Iron |
| Colour | embossed white RAL 9003 |
| Processing | Coating |



100-265 V | topLED 6 W 250 mA | CRI 80
8770

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 12 topped LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 561 lm, with a 93.5 lm/W nominal luminous efficacy and an operating lifetime (L70) of 72.5000 hours.

The diffuser is made of pmma; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 0.55 kg. The power supply driver is included in the delivery.

The total absorbed power is 6 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features

| | |
|---------------------------------------|----------------|
| Luminous flux (source) | 561 lm |
| Colour temperature | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 80 Ra |
| Life / Failure ratio | L70C0B20 72.5H |