


Box_W1



100-265 V | topLED 6 W 250 mA | CRI 80
8771



Technical data	
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	upward
Power	6 W
Luminous flux (source)	561 lm
Frequency	60 - 50 Hz
CCT / Tonaltà	3000 K
Colour rendering index	80 Ra
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	No
CE	No
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	0.55 Kg

Finishing diffuser	
Material	PMMA
Colour	opaline

Finishing mounting frame	
Material	Iron
Colour	Beton dark grey
Processing	Coating



100-265 V | topLED 6 W 250 mA | CRI 80
8771

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 12 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 561 lm, with a 93.5 lm/W nominal luminous efficacy and an operating lifetime (L70) of 72.5000 hours.

The diffuser is made of pmma; the mounting frame is made of iron, with a beton dark grey finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 0.55 kg. The power supply driver is included in the delivery.

The total absorbed power is 6 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features

Luminous flux (source)	561 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Life / Failure ratio	L70C0B20 72.5H